

## • Bakery Case •

Digitally Controlled Uniform Temperature

- \* Life-Up Pneumatic, Cylinder-Assisted Curve Tempered Front Glass.
- \* Sloped Rear Doors for Product Access.
- \* All Welded Base Construction with a Choice of Standard Laminates on Base.  
- Other color laminates optional.
- \* Adjustable Up and Down or Tilted Cantilevered Wire Shelves.
- \* Independently Wired Shelf Lights
- \* Easily Accessible Control Panel
- \* Pull Out Condensing Unit for Easy Service
- \* Four Point Leveling System
- \* TB-4, 5 Non Refrigerated models Available
- \* 304 Stainless Steel Floor and Air Flow Grille
- \* Excellent Cooling Performance: Over-sized Condenser & Evaporator coil
- \* Holds 38°F~ 40°F



TB-4R/TB-5R, TB-4/TB-5



ISO9001

Model	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H	List Price
TB-4R	14.5	3	1/2	11.5	750lbs	47.6 x 37.4 x 47.3	13,195.74
TB-4	14.5	3	-	3.0	690lbs	47.6 x 37.4 x 47.3	8,415.00
TB-5R	18.7	3	1/2	11.5	850lbs	59.5 x 37.4 x 47.3	13,937.28
TB-5	18.7	3	-	4.0	790lbs	59.5 x 37.4 x 47.3	8,899.50

## SPECIFICATIONS

MODEL	TB-4R	TB-4	TB-5R	TB-5
Compressor	1/2 HP	-	1/2 HP	-
Power	115V 60Hz	115V 60Hz	115V 60Hz	115V 60Hz
Amp	11.5 A	3.0 A	11.5 A	4.0 A
Shelves	3	3	3	3
Shipping Weight	780lbs	720lbs	865lbs	805lbs

\*Design and specifications can be changed without prior notice for product improvement.

\*TB models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% relative humidity

\* Self-contained System  
No plumbing required.

\* Foamed with polyurethane, high-density cell insulation (CFC free)

(UNIT : INCH)

